

# FIRE STOPPING

BY NORSEAL

## NORSOUND ACOUSTIC FIRE RATED ACRYLIC

NORSEAL



### Application

Gaps around service penetrations, door castings and sills, fire protection boards and partitioning and low movement construction joints.

### Fixing

Bonds once cured

### Performance

BS EN 1366-3:2009  
BS EN 1366-4:2006  
BS EN 1026:2000  
ASTM E84  
ASTM E2923  
BS EN 13501-2:2016  
LEED 4.1  
BS 476-20  
Suitable for sealing around fire rated FD30 & FD60 doorsets in accordance with BBS 476-22.  
Tested up to 63dB in accordance with BS EN ISO 10140-2:2020.

### Material

Fire rated acrylic sealant

### Colour

White

### Sizes

310ml tube, 600ml foil

### Shelf Life

18 months from date of manufacture

### Order codes

NOR115/W (310ml tube/White)  
NOR115W/F600 (600ml foil/White)

 5 Regents Drive  
Prudhoe  
Northumberland  
NE42 6PX

 [norseal.co.uk](http://norseal.co.uk)

 [firestopping@norseal.co.uk](mailto:firestopping@norseal.co.uk)

 01661 520 930

Registered at Companies House Cardiff No. 04317595 VAT Reg. No. 733 9466 08