

FIRE STOPPING

BY NORSEAL

BLUE 60 FRAME FOAM

BLUE 60



Application

Cavity joints between fire rated door frame and structural opening, not linear gaps

Fixing

Bonds once dry. Must be used in conjunction with Blue 60 fire rated packers

Performance

Fire tested to BS EN 1634-1 & BS 476 Part 22
Acoustically tested up to 43dB

Material

PU foam

Gaps (mm)

Between 7mm and 30mm

Size (mm)

750ml canister

Colour

Blue

Door types

Timber doors - Single and double doorsets.
Tested with softwood, MDF and hardwood frame sections in both metal and timber stud partitionings.

Fire rating

FD30 and FD60

Order codes

BLUE60 - Blue60 fire rated expanding foam (750ml)

BLUE60/12 - Blue60 fire rated expanding foam (750ml/12 pack)

BLUE601X15/GRN


Green fire rated packers (1mm x 15mm x 100mm)

BLUE603X15/WHT


White fire rated packers (3mm x 15mm x 100mm)

BLUE605X15/BLU


Blue fire rated packers (5mm x 15mm x 100mm)




Fire Rated Packer
1mm x 15mm x 100mm
Green



Fire Rated Packer
3mm x 15mm x 100mm
White



Fire Rated Packer
5mm x 15mm x 100mm
Blue

 5 Regents Drive
Prudhoe
Northumberland
NE42 6PX

 norseal.co.uk

 sales@norseal.co.uk

 01661 830088

Registered at Companies House Cardiff No. 04317595 VAT Reg. No. 733 9466 08